


□ SPECIFICATIONS unit=mm

步距角 /STEP ANGLE	1.8° ±5%
相数 /NO. OF PHASES	2
额定电压 /RATED VOLTAGE	3.0 V
额定电流 /RATED CURRENT	3.0 A
电阻 /RESISTANCE	1.0 Ω ±10%
电感 /INDUCTANCE	3.8 mH±20%
静转矩 /HOLDING TORQUE	160N.cm
绝缘等级 /INSULATION CLASS	CLASS B(130° C)
引出线规格 /LEADSTYLE	22AWG UL3266

备注/NOTE:

接线图 / WIRING DIAGRAM



励磁顺序 (2相励磁)
EXCITING SEQUENCE (2EX)

STEP	励磁顺序				CCW
	A	B	Ā	B̄	
1	+	+	-	-	↑
2	-	+	+	-	
3	-	-	+	+	
4	+	-	-	+	

客户确认&接受 CONFIRMED&ACCEPTED BY CUSTOMER					型号/MODEL:
盖章&签名 (COMPANY CHOP&SIGNATURE)					SL57S276A1B-0621
一般公差 TOLERANCE ±0.3/±0.3°	版本 REV	变更番号 ECO NO.	年月日 DATE	变更内容 REVISIONS	设计 BY
制图/DRAWN			比例 SCALE	品名 TITLE	备注 NOTE
设计/DESIGNED			1:1		REV
审核/CHECKED			单位 UNIT		A
承认/APPROVED			mm		
深圳市申力微特电机有限公司 SHENZHEN SHENLI WITT MOTOR CO., LTD					1/1 SHEET